

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Multi Primer 227  
Multigrund 227  
Revision date : 27.03.2023  
Print date : 27.03.2023

Version (Revision) : 23.0.0 (22.0.0)

## SECTION 1: Identification of the substance/mixture and of the company/ undertaking

### 1.1 Product identifier

Multi Primer 227  
Multigrund 227

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

#### Relevant identified uses

##### Products Category [PC]

PC 9 - Coatings and paints, fillers, putties, thinners.

#### Uses advised against

There are no information about relevant identified uses of the product according to the Regulation (EC) No. 1907/2006 (REACH-Regulation), which are advised against. For using the product observe the information in the Technical data sheet of the product.

### 1.3 Details of the supplier of the safety data sheet

#### Supplier

Brillux GmbH & Co KG  
www.brillux.de

**Street :** Weseler Straße 401

**Postal code/City :** D - 48163 Münster

**Telephone :** +49 (0)251-7188-0

**Telefax :** +49 (0)251-7188-280

#### Information contact :

Electronic mail address of the well-informed person for safety data sheets:sdb@brillux.de

### 1.4 Emergency telephone number

Outside the business hours (9 a.m. to 5 p.m.):  
(Giftinformationszentrum-Nord, Göttingen, consultation in german or english language)  
Telephone: +49 (0)551-19240.

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

#### Classification according to Regulation (EC) No 1272/2008 [CLP]

Flam. Liq. 3 ; H226 - Flammable liquids : Category 3 ; Flammable liquid and vapour.

Skin Sens. 1 ; H317 - Skin sensitisation : Category 1 ; May cause an allergic skin reaction.

STOT SE 3 ; H335 - STOT-single exposure : Category 3 ; May cause respiratory irritation.

STOT SE 3 ; H336 - STOT-single exposure : Category 3 ; May cause drowsiness or dizziness.

Aquatic Chronic 2 ; H411 - Hazardous to the aquatic environment : Chronic 2 ; Toxic to aquatic life with long lasting effects.

### 2.2 Label elements

#### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

##### Hazard pictograms



Flame (GHS02) · Environment (GHS09) · Exclamation mark (GHS07)

#### Signal word

Warning

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Multi Primer 227  
Multigrund 227  
Revision date : 27.03.2023  
Print date : 27.03.2023

Version (Revision) : 23.0.0 (22.0.0)

## Hazard components for labelling

HYDROCARBONS, C9, AROMATICS  
REACTION MASS OF ETHYLBENZENE AND XYLENE  
FATTY ACIDS, C18-UNSATURATED, DIMERS, REACTION PRODUCTS WITH N,N-DIMETHYL-1,3-PROPANEDIAMINE AND 1,3-PROPANEDIAMINE ; CAS No. : 162627-17-0

## Hazard statements

H226 Flammable liquid and vapour.  
H317 May cause an allergic skin reaction.  
H335 May cause respiratory irritation.  
H336 May cause drowsiness or dizziness.  
H411 Toxic to aquatic life with long lasting effects.

## Precautionary statements

P102 Keep out of reach of children.  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P261 Avoid breathing spray.  
P271 Use only outdoors or in a well-ventilated area.  
P273 Avoid release to the environment.  
P312 Call a POISON CENTER or a doctor if you feel unwell.  
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.  
P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].  
P391 Collect spillage.  
P501 Dispose of contents/container to approved disposal company or local collection.

## Supplemental hazard information

EUH066 Repeated exposure may cause skin dryness or cracking.

## 2.3 Other hazards

The product does not contain any substances with endocrine-disrupting properties according to Article 59 Paragraph 1 or substances with endocrine-disrupting properties according to Regulations (EU) 2017/2100 or (EU) 2018/605. The product does not contain any substances, which fulfil the criteria for PBT or vPvB in accordance with the Annex XIII of the Regulation (EC) No 1907/2006 (REACH-Regulation).

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

#### Description

Primer based on a PVC-copolymer resin

Composition:

PVC-copolymer resin, alkyd resin, titanium dioxide (depending on the shade), inorganic/organic coloured pigments (depending on the shade), anti-corrosive pigments, zinc white, silicates, aromatic hydrocarbons, aliphatic hydrocarbons, ester, additives and plasticizer.

#### Hazardous ingredients

HYDROCARBONS, C9, AROMATICS ; REACH No. : 01-2119455851-35 ; EC No. : 918-668-5

Weight fraction :  $\geq 15 - < 20$  %

Classification 1272/2008 [CLP] : Flam. Liq. 3 ; H226 Asp. Tox. 1 ; H304 STOT SE 3 ; H335 STOT SE 3 ; H336 Aquatic Chronic 2 ; H411 EUH066

TRIZINC BIS(ORTHOPHOSPHATE) ; REACH No. : 01-2119485044-40 ; EC No. : 231-944-3 ; CAS No. : 7779-90-0

Weight fraction :  $\geq 10 - < 15$  %

Classification 1272/2008 [CLP] : Aquatic Acute 1 ; H400 Aquatic Chronic 1 ; H410

REACTION MASS OF ETHYLBENZENE AND XYLENE ; REACH No. : 01-2119486136-34 ; EC No. : 905-588-0

Weight fraction :  $\geq 5 - < 10$  %

Classification 1272/2008 [CLP] : Flam. Liq. 3 ; H226 Asp. Tox. 1 ; H304 STOT RE 2 ; H373 Acute Tox. 4 ; H312

# Safety Data Sheet

## according to Regulation (EC) No. 1907/2006 (REACH)



**Trade name :** Multi Primer 227  
Multigrund 227  
**Revision date :** 27.03.2023  
**Print date :** 27.03.2023

**Version (Revision) :** 23.0.0 (22.0.0)

Acute Tox. 4 ; H332 Skin Irrit. 2 ; H315 Eye Irrit. 2 ; H319 STOT SE 3 ; H335  
ZINC OXIDE ; REACH No. : 01-2119463881-32 ; EC No. : 215-222-5; CAS No. : 1314-13-2  
Weight fraction :  $\geq 5 - < 10 \%$   
Classification 1272/2008 [CLP] : Aquatic Acute 1 ; H400 Aquatic Chronic 1 ; H410  
HYDROCARBONS, C10-C13, N-ALKANES, ISOALKANES, CYCLICS, < 2% AROMATICS ; REACH No. : 01-2119457273-39 ; EC  
No. : 918-481-9  
Weight fraction :  $\geq 1 - < 5 \%$   
Classification 1272/2008 [CLP] : Asp. Tox. 1 ; H304 EUH066  
N-BUTYL ACETATE ; REACH No. : 01-2119485493-29 ; EC No. : 204-658-1; CAS No. : 123-86-4  
Weight fraction :  $\geq 1 - < 5 \%$   
Classification 1272/2008 [CLP] : Flam. Liq. 3 ; H226 STOT SE 3 ; H336 EUH066  
FATTY ACIDS, C18-UNSATURATED, DIMERS, REACTION PRODUCTS WITH N,N-DIMETHYL-1,3-PROPANEDIAMINE AND 1,3-  
PROPANEDIAMINE ; REACH No. : 01-2119970640-38 ; EC No. : 605-296-0; CAS No. : 162627-17-0  
Weight fraction :  $\geq 0,1 - < 0,5 \%$   
Classification 1272/2008 [CLP] : Skin Sens. 1A ; H317

### Additional information

The used hydrocarbons contain no benzene or benzene in concentrations less than 0.1 percent by weight and fulfil therefore the default(handicap) of the remark P to the appendix VI of the order (EC) No. 1272/2008 (GHS order).  
For full text of Hazard- and EU Hazard-statements: see SECTION 16.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

#### General information

In all cases of doubt, or when symptoms persist, seek medical attention. Immediately remove all contaminated clothing. In case of unconsciousness: lay on side - call a doctor. Never give anything by mouth to an unconscious person. If medical advice is needed, have product container or label at hand.

#### Following inhalation

When symptoms persists, take the casualty into the fresh air and keep warm. Irregular breathing/no breathing: artificial respiration. Call a doctor and tell him the exactly substance.

#### In case of skin contact

Take off immediately all contaminated clothes. Wash away with soap and water and rinse. Do NOT use solvents or thinners. If skin irritation continues, consult a doctor.

#### After eye contact

Remove contact lenses, keep eyelids open. Rinse open eye immediately with plenty of running water. Seek medical advice if complaint continues.

#### Following ingestion

Drink water in small draught. Keep at rest. Do not induce vomiting. When swallowed immediately consult and show packing or label to physician.

### 4.2 Most important symptoms and effects, both acute and delayed

Potential symptoms: Headache, dizziness, giddiness, skin irritation, eye irritation and irritation to respiratory tract are possible. Allergic symptoms.

### 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

#### Suitable extinguishing media

In case of fire: Use alcohol resistant foam, CO<sub>2</sub>, powders or water spray for extinction.

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Multi Primer 227  
Multigrund 227  
Revision date : 27.03.2023  
Print date : 27.03.2023

Version (Revision) : 23.0.0 (22.0.0)

## Unsuitable extinguishing media

In case of fire: Do not use waterjet for extinction.

## 5.2 Special hazards arising from the substance or mixture

### Hazardous combustion products

Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard.

## 5.3 Advice for firefighters

### Special protective equipment for firefighters

At a fire caused by the product a breathing apparatus with an independent source of air is to have ready and to use if necessary for the firefighting. Personnel should wear protective clothings.

## 5.4 Additional information

Cool endangered containers with water in case of fire. Do not allow run-off from fire-fighting to enter drains or water courses.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Refer to protective measures listed in sections 7 and 8. Keep away from ignition sources on account of the organic solvent content and air room well. Do not inhale vapours. Avoid contact with eyes and skin.

### 6.2 Environmental precautions

Do not empty into drains. If the product contaminates lakes, rivers or sewages, inform appropriate authorities in accordance with local regulations. Holding polluted washing water back and disposing of duly.

### 6.3 Methods and material for containment and cleaning up

#### For cleaning up

Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations (see section 13). The areas concerned cleaning with a customary water based cleaning agent, not using organic solvents if possible.

### 6.4 Reference to other sections

See Section 7 for information on safe handling.  
You find information about the safety equipment of persons in the section 8,  
information about the refuse disposal in section 13.

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

#### Protective measures

Ensure a good ventilation in room and working area. Prevent the creation of inflammable or explosive concentrations of vapour in air and avoid vapour concentrations higher than the OEL (=Occupational Exposure Limit). Only use the material in places where open light, fire and other flammable sources can be kept away. For personal protection see Section 8. Avoid contact with skin and eyes. Read label before use.

#### Measures to prevent fire

Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air. Avoid concentrations which form ignitable or explosive vapour and air mixtures. Likewise, avoid any concentration of vapour above the MAC-value. Keep away from ignition sources - No smoking. Ground/bond container and receiving equipment. Use explosion-proof pipes, electrical, ventilating and lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge.

#### Measures to prevent aerosol and dust generation

Do not breathe gas or spray.

#### Advices on general occupational hygiene

While working do not eat, drink or smoke. Wash hands and face before breaks and after work and take a shower if necessary. Immediately remove all contaminated clothing.

### 7.2 Conditions for safe storage, including any incompatibilities

**Trade name :** Multi Primer 227  
Multigrund 227  
**Revision date :** 27.03.2023  
**Print date :** 27.03.2023

**Version (Revision) :** 23.0.0 (22.0.0)

### Requirements for storage rooms and vessels

Electrical equipment should be protected to the appropriate standard. Floors should be of the conducting type. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Never use pressure to empty: container is not a pressure vessel. No smoking. Prevent unauthorized access. Do not store the product in lounge room. Keep only in the original container. Keep out of the reach of children. Store in a well-ventilated place. Keep cool.

### Hints on joint storage

Keep away from oxidizing agents, from strongly alkaline and strongly acid materials. Store away from foodstuffs.

**Storage class (TRGS 510) :** 3

### Further information on storage conditions

Keep container tightly sealed. Store at 5°-35°C. Containers should be kept dry and sealed.

### 7.3 Specific end use(s)

For using the product observe the information in the Technical data sheet of the product.

### Industrial sector specific solutions

**GISCODE :** Product code in accordance with GISBAU (hazardous materials information system of the German professional associations of the building and construction industry) for colours and varnishes (GISCODE): BSL50

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational exposure limit values

HYDROCARBONS, C9, AROMATICS

Limit value type (country of origin) : TRGS 900 ( D )

Parameter : Group limit for the calculation of the occupational exposure limit for hydrocarbon mixtures (see section 2.9 of Technical Rule 900).

Limit value : 50 mg/m<sup>3</sup>

Version :

REACTION MASS OF ETHYLBENZENE AND XYLENE

Limit value type (country of origin) : TRGS 900 ( D )

Limit value : 100 ppm / 440 mg/m<sup>3</sup>

Peak limitation : 4

Remark : Xylol

Version : 01.10.1993

Limit value type (country of origin) : TRGS 900 ( D )

Limit value : 20 ppm / 88 mg/m<sup>3</sup>

Peak limitation : 2(II)

Remark : Ethylbenzol H, Y, DFG

Version : 01.10.1993

Limit value type (country of origin) : STEL ( EC )

Limit value : 200 ppm / 884 mg/m<sup>3</sup>

Remark : Ethylbenzol H

Version :

Limit value type (country of origin) : TWA ( EC )

Limit value : 100 ppm / 442 mg/m<sup>3</sup>

Remark : Ethylbenzol H

Version :

HYDROCARBONS, C10-C13, N-ALKANES, ISOALKANES, CYCLICS, < 2% AROMATICS

Limit value type (country of origin) : TRGS 900 ( D )

Parameter : Group limit for the calculation of the occupational exposure limit for hydrocarbon mixtures (see section 2.9 of Technical Rule 900).

Limit value : 300 mg/m<sup>3</sup>

Version :

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



**Trade name :** Multi Primer 227  
Multigrund 227  
**Revision date :** 27.03.2023  
**Print date :** 27.03.2023

**Version (Revision) :** 23.0.0 (22.0.0)

N-BUTYL ACETATE ; CAS No. : 123-86-4

Limit value type (country of origin) : TRGS 900 ( D )  
Limit value : 62 ppm / 300 mg/m<sup>3</sup>  
Peak limitation : 2(I)  
Remark : Y  
Version : 02.07.2021

Limit value type (country of origin) : STEL ( EC )  
Limit value : 150 ppm / 723 mg/m<sup>3</sup>  
Version : 20.06.2019

Limit value type (country of origin) : TWA ( EC )  
Limit value : 50 ppm / 241 mg/m<sup>3</sup>  
Version : 20.06.2019

## Remark

Short time value (STEL): Excess factor 2 (II) according to the german TRGS 900.  
Taking into account the details mentioned in the TRGS 900 for the supervision of AGW.

## Biological limit values

REACTION MASS OF ETHYLBENZENE AND XYLENE

Limit value type (country of origin) : TRGS 903 ( D )  
Parameter : Xylene / Whole blood (B) / End of exposure or end of shift  
Limit value : 0,15 mg/dl  
Remark : Xylol  
Version : 01.10.1993

Limit value type (country of origin) : TRGS 903 ( D )  
Parameter : Methylhippuric (toluric) acid (all isomers) / Urine (U) / End of exposure or end of shift  
Limit value : 2 g/l  
Remark : Xylol  
Version : 01.10.1993

Limit value type (country of origin) : TRGS 903 ( D )  
Parameter : Ethylbenzene / Whole blood (B) / End of exposure or end of shift  
Limit value : 1 mg/l  
Remark : Ethylbenzol  
Version : 01.10.1993

Limit value type (country of origin) : TRGS 903 ( D )  
Parameter : Mandelic acid plus phenylglyoxylic acid / Urine (U) / End of exposure or end of shift  
Limit value : 800 mg/g Creatinine  
Remark : Ethylbenzol  
Version : 01.10.1993

## DNEL-/PNEC-values

### DNEL/DMEL

HYDROCARBONS, C9, AROMATICS

Limit value type : DNEL/DMEL (Consumer)  
Exposure route : Dermal  
Exposure frequency : Long-term  
Limit value : 11 mg/kg  
Assessment factor : 1 D  
Limit value type : DNEL/DMEL (Consumer)  
Exposure route : Inhalation  
Exposure frequency : Long-term  
Limit value : 32 mg/m<sup>3</sup>  
Limit value type : DNEL/DMEL (Consumer)  
Exposure route : Oral  
Exposure frequency : Long-term  
Limit value : 11 mg/kg

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



**Trade name :** Multi Primer 227  
Multigrund 227

**Revision date :** 27.03.2023

**Print date :** 27.03.2023

**Version (Revision) :** 23.0.0 (22.0.0)

Assessment factor : 1 D  
Limit value type : DNEL/DMEL (Professional)  
Exposure route : Dermal  
Exposure frequency : Long-term  
Limit value : 25 mg/kg  
Assessment factor : 1 D  
Limit value type : DNEL/DMEL (Professional)  
Exposure route : Inhalation  
Exposure frequency : Long-term  
Limit value : 150 mg/m<sup>3</sup>

TRIZINC BIS(ORTHOPHOSPHATE) ; CAS No. : 7779-90-0

Limit value type : DNEL/DMEL (Consumer)  
Exposure route : Dermal  
Exposure frequency : Long-term  
Limit value : 83 mg/kg  
Assessment factor : 1 day(s)  
Limit value type : DNEL/DMEL (Consumer)  
Exposure route : Inhalation  
Exposure frequency : Long-term  
Limit value : 2,5 mg/m<sup>3</sup>  
Limit value type : DNEL/DMEL (Consumer)  
Exposure route : Oral  
Exposure frequency : Long-term  
Limit value : 0,83 mg/kg  
Assessment factor : 1 day(s)  
Limit value type : DNEL/DMEL (Worker)  
Exposure route : Inhalation  
Exposure frequency : Long-term  
Limit value : 5 mg/m<sup>3</sup>  
Limit value type : DNEL/DMEL (Worker)  
Exposure route : Dermal  
Exposure frequency : Long-term  
Limit value : 83 mg/kg  
Assessment factor : 1 day(s)

REACTION MASS OF ETHYLBENZENE AND XYLENE

Limit value type : DNEL Consumer (local)  
Exposure route : Inhalation  
Exposure frequency : Long-term  
Limit value : = 65,3 mg/m<sup>3</sup>  
Limit value type : DNEL Consumer (local)  
Exposure route : Inhalation  
Exposure frequency : Short-term  
Limit value : = 260 mg/m<sup>3</sup>  
Limit value type : DNEL Consumer (systemic)  
Exposure route : Oral  
Exposure frequency : Long-term  
Limit value : = 1,6 mg/kg  
Assessment factor : 1 D  
Limit value type : DNEL Consumer (systemic)  
Exposure route : Inhalation  
Exposure frequency : Long-term  
Limit value : = 14,8 mg/m<sup>3</sup>  
Limit value type : DNEL Consumer (systemic)  
Exposure route : Inhalation  
Exposure frequency : Short-term

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



**Trade name :** Multi Primer 227  
Multigrund 227  
**Revision date :** 27.03.2023  
**Print date :** 27.03.2023

**Version (Revision) :** 23.0.0 (22.0.0)

Limit value : = 260 mg/m<sup>3</sup>  
Limit value type : DNEL worker (local)  
Exposure route : Inhalation  
Exposure frequency : Short-term  
Limit value : = 289 mg/m<sup>3</sup>  
Limit value type : DNEL worker (local and systemic)  
Exposure route : Inhalation  
Exposure frequency : Long-term  
Limit value : = 221 mg/m<sup>3</sup>  
Limit value type : DNEL worker (systemic)  
Exposure route : Inhalation  
Exposure frequency : Long-term  
Limit value : = 211 mg/m<sup>3</sup>  
Limit value type : DNEL worker (systemic)  
Exposure route : Inhalation  
Exposure frequency : Short-term  
Limit value : = 442 mg/m<sup>3</sup>  
Limit value type : DNEL worker (systemic)  
Exposure route : Dermal  
Exposure frequency : Long-term  
Limit value : = 180 mg/kg  
Assessment factor : 1 D

ZINC OXIDE ; CAS No. : 1314-13-2  
Limit value type : DNEL/DMEL (Industrial)  
Exposure route : Inhalation  
Exposure frequency : Long-term  
Limit value : 5 mg/m<sup>3</sup>  
Limit value type : DNEL/DMEL (Industrial)  
Exposure route : Dermal  
Exposure frequency : Long-term  
Limit value : 83 mg/kg

N-BUTYL ACETATE ; CAS No. : 123-86-4  
Limit value type : DNEL Consumer (systemic)  
Exposure route : Inhalation  
Exposure frequency : Long-term  
Limit value : 102,34 mg/m<sup>3</sup>  
Limit value type : DNEL/DMEL (Industrial)  
Exposure route : Inhalation  
Exposure frequency : Short-term  
Limit value : 96 mg/kg  
Limit value type : DNEL/DMEL (Industrial)  
Exposure route : Inhalation  
Exposure frequency : Long-term  
Limit value : 48 mg/m<sup>3</sup>  
Limit value type : DNEL/DMEL (Industrial)  
Exposure route : Dermal  
Exposure frequency : Long-term  
Limit value : 7 mg/kg  
Limit value type : DNEL/DMEL (Industrial)  
Exposure route : Inhalation  
Exposure frequency : Long-term  
Limit value : 480 mg/m<sup>3</sup>

## PNEC

TRIZINC BIS(ORTHOPHOSPHATE) ; CAS No. : 7779-90-0  
Limit value type : PNEC (Aquatic, freshwater)



# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



**Trade name :** Multi Primer 227  
Multigrund 227

**Revision date :** 27.03.2023

**Print date :** 27.03.2023

**Version (Revision) :** 23.0.0 (22.0.0)

Limit value : 20,6 µg/l  
Limit value type : PNEC (Aquatic, marine water)  
Limit value : 6,1 µg/l  
Limit value type : PNEC (Sediment, freshwater)  
Limit value : 117,8 µg/l  
Limit value type : PNEC (Sediment, marine water)  
Limit value : 56,5 µg/l  
Limit value type : PNEC soil  
Exposure route : Soil  
Limit value : 35,6 mg/kg  
Limit value type : PNEC (Sewage treatment plant)  
Limit value : 100 µg/l

#### REACTION MASS OF ETHYLBENZENE AND XYLENE

Limit value type : PNEC (Aquatic, freshwater)  
Exposure route : Water (Including sewage plant)  
Limit value : 0,327 mg/l  
Limit value type : PNEC (Aquatic, marine water)  
Exposure route : Water (Including sewage plant)  
Limit value : = 0,327 mg/l  
Limit value type : PNEC (Sediment, freshwater)  
Exposure route : Water (Including sewage plant)  
Limit value : 12,64 mg/kg  
Limit value type : PNEC (Sediment, marine water)  
Exposure route : Water (Including sewage plant)  
Limit value : = 12,64 mg/kg  
Limit value type : PNEC soil  
Exposure route : Soil  
Limit value : 2,31 mg/kg  
Limit value type : PNEC (Sewage treatment plant)  
Exposure route : Water (Including sewage plant)  
Limit value : 6,58 mg/l

#### ZINC OXIDE ; CAS No. : 1314-13-2

Limit value type : PNEC (Industrial)  
Exposure route : Water (Including sewage plant)  
Limit value : 20,6 µg/l  
Limit value type : PNEC (Industrial)  
Exposure route : Soil  
Limit value : 35,6 mg/kg

#### N-BUTYL ACETATE ; CAS No. : 123-86-4

Limit value type : PNEC (Aquatic, freshwater)  
Exposure route : Water (Including sewage plant)  
Limit value : 0,18 mg/l  
Limit value type : PNEC (Aquatic, intermittent release)  
Exposure route : Water (Including sewage plant)  
Limit value : 0,36 mg/l  
Limit value type : PNEC (Aquatic, marine water)  
Exposure route : Water (Including sewage plant)  
Limit value : 0,018 mg/l  
Limit value type : PNEC (Sediment, freshwater)  
Exposure route : Soil  
Limit value : 0,981 mg/kg  
Limit value type : PNEC (Sediment, marine water)  
Exposure route : Soil  
Limit value : 0,0981 mg/kg  
Limit value type : PNEC soil

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Multi Primer 227  
Multigrund 227  
Revision date : 27.03.2023  
Print date : 27.03.2023

Version (Revision) : 23.0.0 (22.0.0)

Exposure route : Soil  
Limit value : 0,0903 mg/kg  
Limit value type : PNEC (Sewage treatment plant)  
Exposure route : Water (Including sewage plant)  
Limit value : 35,6 mg/l

## 8.2 Exposure controls

### Appropriate engineering controls

Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapour below the OEL (=Occupational Exposure Limit), suitable respiratory protection must be worn. Observe data available of section 7.

### Personal protection equipment

#### Eye/face protection

Use protection glasses in case of spattering.

#### Skin protection

##### Hand protection

At use as agreed a protective gloves from nitrile rubber with a material thickness 0,38 mm has to be used. Notes of the manufacturer have to be taken into account. Penetration time of the glove material: > = 60 min.

By longer or repeated contact the penetration times can be considerably shorter. The protective gloves should be replaced after the first wear out or a damage of the gloves. Gloves of cotton should be used under the gloves of polychloropren or nitrile rubber. After washing hands replace lost skin fat by fat containing skin creams.

##### Body protection

Using protective clothing. If the product must sprayed, use a disposable protective suit.

#### Respiratory protection

Breathing protection equipment is not required in good ventilated places. A respiratory protection (combination filter A2-P3) is required by inadequate ventilation and by spray application. Do not breathe gas or spray.

### General information

Avoid contact with eyes and skin. Immediately remove all contaminated clothing. Do not eat or drink during work - no smoking. Wash hands before breaks and after work. Ensure a good ventilation in room and working area. Do not breathe gas or spray.

### Environmental exposure controls

The product should not reach waters and the ground. If the product contaminates lakes, rivers or sewages, inform appropriate authorities in accordance with local regulations.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

#### Appearance

Physical state : Liquid.

Colour : conformable to product designation.

#### Odour

aromatic ester-like

#### Safety characteristics

Melting point/freezing point :	( 1013 hPa )	No data available
Initial boiling point and boiling range :	( 1013 hPa )	124 - 180 °C
Decomposition temperature :	( 1013 hPa )	No data available
Flash point :		25 °C
Auto-ignition temperature :	>	400 °C
Lower explosion limit :		0,8 Vol-%
Upper explosion limit :		7,5 Vol-%

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Multi Primer 227  
Multigrund 227  
Revision date : 27.03.2023  
Print date : 27.03.2023

Version (Revision) : 23.0.0 (22.0.0)

Vapour pressure :	( 50 °C )	45	hPa
Density :	( 20 °C )	1,4 - 1,5	g/cm <sup>3</sup>
Solvent separation test :	( 20 °C )	<	3 %
Water solubility :	( 20 °C )		practically insoluble
pH :			not applicable
log P O/W :			No data available
Flow time :	( 20 °C )		No data available
Viscosity :	( 20 °C )		thixotropic
Kinematic viscosity :	( 40 °C )	>	20,5 mm <sup>2</sup> /s
Relative vapour density :	( 20 °C )		No data available
VOC-value :		max.	500 g/l
Flammable liquids :	The product is ignitable.		
Particle Characteristics :	not applicable		

## 9.2 Other information

Other physical and chemical data have not been determined.

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

No dangers connected by a possible reactivity of the product are known to proper handling and storage.

### 10.2 Chemical stability

Stable under recommended storage and handling conditions (see section 7).

### 10.3 Possibility of hazardous reactions

Vapours can form explosive mixtures with air.

### 10.4 Conditions to avoid

To avoid formation of ignitable vapour and air mixtures ensure good ventilation (inter alia extraction system). Keep away from frost, heat and direct sunlight.

Cleaning cloths saturated with solvent can ignite themselves. Therefore ensure safe disposal of waste.

### 10.5 Incompatible materials

No dangerous reaction known. Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

### 10.6 Hazardous decomposition products

No dangerous decomposition product are known if stored and handled correctly. When exposed to high temperatures or in case of fire hazardous decomposition products such as carbon monoxide and dioxide, smoke, oxides of nitrogen, may produced.

## SECTION 11: Toxicological information

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Acute toxicity

Acute toxicity:

- Acute oral toxicity: No data available;
- Acute dermal toxicity: No data available;
- Acute inhalation toxicity: No data available.

#### Acute oral toxicity

Parameter :	ATEmix calculated
Exposure route :	Oral
Effective dose :	not relevant
Parameter :	LD50 ( HYDROCARBONS, C9, AROMATICS )
Exposure route :	Oral
Species :	Rat
Effective dose :	> 6800 mg/kg

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



**Trade name :** Multi Primer 227  
Multigrund 227

**Revision date :** 27.03.2023

**Print date :** 27.03.2023

**Version (Revision) :** 23.0.0 (22.0.0)

Parameter : LD50 ( TRIZINC BIS(ORTHOPHOSPHATE) ; CAS No. : 7779-90-0 )  
Exposure route : Oral  
Species : Rat  
Effective dose : > 5000 mg/kg

Parameter : LD50 ( REACTION MASS OF ETHYLBENZENE AND XYLENE )  
Exposure route : Oral  
Species : Rat  
Effective dose : 3523 - 4000 mg/kg

Parameter : LD50 ( ZINC OXIDE ; CAS No. : 1314-13-2 )  
Exposure route : Oral  
Species : Rat  
Effective dose : > 5000 mg/kg

Parameter : LD50 ( HYDROCARBONS, C10-C13, N-ALKANES, ISOALKANES, CYCLICS, < 2% AROMATICS )  
Exposure route : Oral  
Species : Rat  
Effective dose : > 5000 mg/kg

Parameter : LD50 ( N-BUTYL ACETATE ; CAS No. : 123-86-4 )  
Exposure route : Oral  
Species : Rat  
Effective dose : 10760 mg/kg

#### Acute dermal toxicity

Parameter : ATEmix calculated  
Exposure route : Dermal  
Effective dose : 16094 mg/kg

Parameter : LD50 ( HYDROCARBONS, C9, AROMATICS )  
Exposure route : Dermal  
Species : Rabbit  
Effective dose : > 3400 mg/kg

Parameter : LD50 ( REACTION MASS OF ETHYLBENZENE AND XYLENE )  
Exposure route : Dermal  
Species : Rabbit  
Effective dose : 12126 mg/kg

Parameter : LD50 ( ZINC OXIDE ; CAS No. : 1314-13-2 )  
Exposure route : Dermal  
Species : Rat  
Effective dose : > 2000 mg/kg

Parameter : LD50 ( HYDROCARBONS, C10-C13, N-ALKANES, ISOALKANES, CYCLICS, < 2% AROMATICS )  
Exposure route : Dermal  
Species : Rabbit  
Effective dose : > 5000 mg/kg

Parameter : LD50 ( N-BUTYL ACETATE ; CAS No. : 123-86-4 )  
Exposure route : Dermal  
Species : Rabbit  
Effective dose : > 14000 mg/kg

#### Acute inhalation toxicity

Parameter : ATEmix calculated  
Exposure route : Inhalation (vapour)  
Effective dose : 160,9 mg/l

Parameter : LC50 ( HYDROCARBONS, C9, AROMATICS )  
Exposure route : Inhalation  
Species : Rat  
Effective dose : > 10,2 mg/l  
Exposure time : 4 h

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Multi Primer 227  
Multigrund 227  
Revision date : 27.03.2023  
Print date : 27.03.2023

Version (Revision) : 23.0.0 (22.0.0)

Parameter :	LC50 ( TRIZINC BIS(ORTHOPHOSPHATE) ; CAS No. : 7779-90-0 )
Exposure route :	Inhalation
Species :	Rat
Effective dose :	> 5,7 mg/l
Exposure time :	4 h
Parameter :	LC50 ( REACTION MASS OF ETHYLBENZENE AND XYLENE )
Exposure route :	Inhalation (vapour)
Species :	Rat
Effective dose :	10 - 20 mg/l
Exposure time :	4 h
Parameter :	LC50 ( ZINC OXIDE ; CAS No. : 1314-13-2 )
Exposure route :	Inhalation
Species :	Rat
Effective dose :	5,7 mg/l
Parameter :	LC50 ( HYDROCARBONS, C10-C13, N-ALKANES, ISOALKANES, CYCLICS, < 2% AROMATICS )
Exposure route :	Inhalation
Species :	Rat
Effective dose :	> 4,951 mg/l
Exposure time :	4 h
Parameter :	LC50 ( N-BUTYL ACETATE ; CAS No. : 123-86-4 )
Exposure route :	Inhalation
Species :	Rat
Effective dose :	23,4 mg/kg
Exposure time :	4 h

## Corrosion

Irritant effect:

- On the skin: May cause irritation to the skin.
- On the eye: May cause eye irritation.
- Respiratory: May cause irritation to the respiratory tract.

## Respiratory or skin sensitisation

The product is labeled as skin sensitizing.

## CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

The product is not classified as human germ cell mutagenic, carcinogenic or human reproductive toxic (CMR effects).

## STOT-single exposure

Exposure to component solvents vapours concentration in excess of the stated occupational exposure limit may result in adverse health effect such as mucous membrane and respiratory system irritation, kidneys and liver damages, as well as leading the impairment of the central nervous system.

Symptoms and signs include headache: dizziness, fatigue, muscular weakness, drowsiness and in extreme cases loss of consciousness.

The liquid splashed in the eyes may cause irritation and reversible damage.

## STOT-repeated exposure

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and absorption through the skin.

## Aspiration hazard

The product contains substances, which are classified as aspiration toxicity, category 1 (May be fatal if swallowed and enters airways), in accordance to the Regulation (EC) No. 1272/2008 (CLP-Regulation) in their pure form. Based on available data the classification criteria according to Regulation (EC) No 1272/2008 [CLP] are not fulfilled.

## 11.2 Information on other hazards

### Endocrine disrupting properties

The product does not contain any substances with endocrine-disrupting properties according to Article 59 Paragraph 1 or substances with endocrine-disrupting properties according to Regulations (EU) 2017/2100 or (EU) 2018/605.

### Other adverse effects

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Multi Primer 227  
Multigrund 227  
Revision date : 27.03.2023  
Print date : 27.03.2023

Version (Revision) : 23.0.0 (22.0.0)

This product is unlikely to harm health, given normal and proper handling and hygienic precautions.

## Additional information

The product is classified in toxicological terms on the basis of the results of the calculation procedure outlined within the Regulation (EC) No 1272/2008 (CLP-Regulation), listed in sections 2 and 3.  
At proper dealing and use as agreed the product does not cause any effects bad for health after our experiences and the information submitted to us.

## SECTION 12: Ecological information

### 12.1 Toxicity

#### Aquatic toxicity

##### Acute (short-term) fish toxicity

Parameter :	LC50 ( HYDROCARBONS, C9, AROMATICS )
Species :	Oncorhynchus mykiss (Rainbow trout)
Effective dose :	9,2 mg/l
Exposure time :	96 h
Parameter :	LC50 ( REACTION MASS OF ETHYLBENZENE AND XYLENE )
Species :	Acute (short-term) fish toxicity
Evaluation parameter :	Oncorhynchus mykiss
Effective dose :	= 2,6 mg/l
Exposure time :	96 h
Parameter :	LC50 ( ZINC OXIDE ; CAS No. : 1314-13-2 )
Species :	Oncorhynchus mykiss (Rainbow trout)
Effective dose :	0,14 mg/l
Exposure time :	96 h
Parameter :	LC50 ( N-BUTYL ACETATE ; CAS No. : 123-86-4 )
Species :	Pimephales promelas (fathead minnow)
Effective dose :	18 mg/l
Exposure time :	96 h

##### Acute (short-term) toxicity to crustacea

Parameter :	EC50 ( HYDROCARBONS, C9, AROMATICS )
Species :	Daphnia magna (Big water flea)
Effective dose :	3,2 mg/l
Exposure time :	48 h
Parameter :	EC50 ( TRIZINC BIS(ORTHOPHOSPHATE) ; CAS No. : 7779-90-0 )
Species :	Ceriodaphnia spec
Effective dose :	2,44 mg/l
Exposure time :	48 h
Parameter :	LC50 ( REACTION MASS OF ETHYLBENZENE AND XYLENE )
Species :	Acute (short-term) toxicity to crustacea
Evaluation parameter :	Daphnia magna
Effective dose :	= 1 mg/l
Exposure time :	24 h
Parameter :	EC50 ( ZINC OXIDE ; CAS No. : 1314-13-2 )
Species :	Daphnia magna (Big water flea)
Effective dose :	0,17 mg/l
Exposure time :	48 h
Parameter :	EC50 ( N-BUTYL ACETATE ; CAS No. : 123-86-4 )
Species :	Daphnia magna (Big water flea)
Effective dose :	44 mg/l
Exposure time :	48 h

##### Acute (short-term) toxicity to algae and cyanobacteria

Parameter :	ErC50 ( HYDROCARBONS, C9, AROMATICS )
Species :	Pseudokirchneriella subcapitata

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Multi Primer 227  
Multigrund 227  
Revision date : 27.03.2023  
Print date : 27.03.2023

Version (Revision) : 23.0.0 (22.0.0)

Effective dose : 2,6 - 2,9 mg/l  
Exposure time : 72 h  
Parameter : ErC50 ( TRIZINC BIS(ORTHOPHOSPHATE) ; CAS No. : 7779-90-0 )  
Species : Selenastrum capricornutum  
Effective dose : 0,8 mg/l  
Exposure time : 72 h  
Parameter : EC50 ( REACTION MASS OF ETHYLBENZENE AND XYLENE )  
Species : Scenedesmus capricornutum  
Evaluation parameter : Acute (short-term) toxicity to algae and cyanobacteria  
Effective dose : = 2,2 mg/l  
Exposure time : 73 h  
Parameter : IC50 ( ZINC OXIDE ; CAS No. : 1314-13-2 )  
Species : Scenedesmus capricornutum  
Effective dose : 0,14 mg/l  
Exposure time : 72 h  
Parameter : EL0 ( HYDROCARBONS, C10-C13, N-ALKANES, ISOALKANES, CYCLICS, < 2% AROMATICS )  
Species : Daphnia magna (Big water flea)  
Effective dose : 1000 mg/l  
Exposure time : 48 h  
Parameter : EL0 ( HYDROCARBONS, C10-C13, N-ALKANES, ISOALKANES, CYCLICS, < 2% AROMATICS )  
Species : Pseudokirchneriella subcapitata  
Effective dose : 1000 mg/l  
Exposure time : 72 h  
Parameter : EC50 ( N-BUTYL ACETATE ; CAS No. : 123-86-4 )  
Species : Desmodesmus subspicatus  
Effective dose : 647,7 mg/l  
Exposure time : 72 h  
Parameter : EL50 ( N-BUTYL ACETATE ; CAS No. : 123-86-4 )  
Species : Desmodesmus subspicatus  
Effective dose : 200 mg/l

### Toxicity to microorganisms

Parameter : EL50 ( TRIZINC BIS(ORTHOPHOSPHATE) ; CAS No. : 7779-90-0 )  
Species : Mysisopsis bahia  
Effective dose : 0,1 mg/l  
Exposure time : 4 h

### Sewage treatment plant

Parameter : Effects in sewage plants ( REACTION MASS OF ETHYLBENZENE AND XYLENE )  
Inoculum : Activated sludge  
Effective dose : = 16 mg/l  
Exposure time : 28 D

## 12.2 Persistence and degradability

These are not data available about the potential of the product concerning his persistency and degradability.

### Biodegradation

Parameter : Biodegradation ( REACTION MASS OF ETHYLBENZENE AND XYLENE )  
Inoculum : Biodegradation  
Evaluation parameter : Aerobic  
Degradation rate : = 90 %  
Test duration : 28 D

## 12.3 Bioaccumulative potential

Parameter : Bioconcentration factor (BCF) ( REACTION MASS OF ETHYLBENZENE AND XYLENE )  
Bioconcentration factor (BCF)  
Value : = 25,9

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



**Trade name :** Multi Primer 227  
Multigrund 227

**Revision date :** 27.03.2023

**Print date :** 27.03.2023

**Version (Revision) :** 23.0.0 (22.0.0)

These are not data available about the bio accumulation potential of the product.

## 12.4 Mobility in soil

These are not data available about the potential of the product concerning his mobility in the ground. A penetrating into soil, waters and sewage system should be prevented.

## 12.5 Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

## 12.6 Endocrine disrupting properties

The product does not contain any substances with endocrine-disrupting properties according to Article 59 Paragraph 1 or substances with endocrine-disrupting properties according to Regulations (EU) 2017/2100 or (EU) 2018/605.

## 12.7 Other adverse effects

Toxic to aquatic life. May cause long-term adverse effects in the aquatic environment.

## 12.8 Additional ecotoxicological information

Avoid exposing into ground, waterways and drainage.  
The classification of the product is based on summation of classified components according to the Regulation (EC) No 1272/2008 (CLP-Regulation). See details in sections 2 and 3.

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

#### Directive 2008/98/EC (Waste Framework Directive)

##### Before intended use

Dispose of contents/container to approved disposal company or local collection according to the local regulations. Packaging with not dry uped residues have to dropped at official collecting sites. Packaging with dry uped residues can be disposed together with household garbage or building site garbage. Do not empty into waters or drains.

##### Waste codes/waste designations according to EWC/AVV

For the product:

Disposal-definition No.: 08 01 11\* - Paint and varnish waste which contains organic solvents or other dangerous substances.

##### After intended use

Only empty packaging can be transfered to recycling. Uncleaned packaging must be disposed of in the same manner as the medium.

##### Waste codes/waste designations according to EWC/AVV

For the uncleaned packaging:

Disposal-definition No.: 15 01 10\* - packaging containing residues of or contaminated by hazardous substances.

## SECTION 14: Transport information

### 14.1 UN number

UN 1263

### 14.2 UN proper shipping name

#### Land transport (ADR/RID)

PAINT

#### Sea transport (IMDG)

PAINT ( TRIZINC BIS(ORTHOPHOSPHATE) )

#### Air transport (ICAO-TI / IATA-DGR)

PAINT

### 14.3 Transport hazard class(es)

#### Land transport (ADR/RID)

**Class(es) :** 3  
**Classification code :** F1  
**Hazard identification number (Kemler)** 30



# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Multi Primer 227  
Multigrund 227  
Revision date : 27.03.2023  
Print date : 27.03.2023

Version (Revision) : 23.0.0 (22.0.0)

No.) :  
Tunnel restriction code : D/E  
Special provisions : LQ 5 I · E 1 · ADR : - (<= 5 l ; 2.2.3.1.5 + N)  
Hazard label(s) : 3 / N  
Sea transport (IMDG)  
Class(es) : 3  
EmS-No. : F-E / S-E  
Special provisions : LQ 5 I · E 1 · IMDG 2.3.2.5 + P (<= 5 l)  
Hazard label(s) : 3 / N  
Air transport (ICAO-TI / IATA-DGR)  
Class(es) : 3  
Special provisions : E 1  
Hazard label(s) : 3

#### 14.4 Packing group

III

#### 14.5 Environmental hazards

Land transport (ADR/RID) : Yes  
Sea transport (IMDG) : Yes (P)  
Air transport (ICAO-TI / IATA-DGR) : Yes

#### 14.6 Special precautions for user

None

#### 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not relevant because the product in type of delivery does not transport in bulks according to the International Maritime Organization (IMO) instruments.

#### 14.8 Additional information

The transport in containers with max. 5 litres contents are not subject to the regulations of ADR/RID.  
According to the transport regulations the product is labeling with the label 3 and in packages > 5 ltr.with the symbol "Fish and tree".

### SECTION 15: Regulatory information

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

##### EU legislation

###### Authorisations and/or restrictions on use

###### Restrictions on use

###### Regulation (EC) No. 1907/2006 (REACH), Annex XVII (restrictions):

Use restriction according to REACH annex XVII, no. : 3, 40, 75

###### Other regulations (EU)

###### Directive 2004/42/EC on the limitation of emissions of volatile organic compounds

Product sub-category and VOC limiting values in accordance with appendix II, letter A of the guideline:

Category i, type Lb;

VOC limiting value of the category for 2010: 500 g/l.

This product contains max. 500 g/l VOC.

###### National regulations

###### Water hazard class

Classification according to AwSV - Class : 2 (Obviously hazardous to water)

###### Additional information

The product is classified as a solid substance according to the criteria of the Penetrometer test (ADR, part 2, section 2.3.4) and also fulfils the criteria for solid substances according to the TRwS 779 number 2.1.1.

Maternity regulations and Young Persons Employment Act are to take into account.

# Safety Data Sheet

## according to Regulation (EC) No. 1907/2006 (REACH)



**Trade name :** Multi Primer 227  
Multigrund 227

**Revision date :** 27.03.2023

**Print date :** 27.03.2023

**Version (Revision) :** 23.0.0 (22.0.0)

### 15.2 Chemical Safety Assessment

A chemical safety assessments was not carried out.

## SECTION 16: Other information

### 16.1 Indication of changes

02. Label elements · 15. Restrictions on use · 15. Water hazard class

### 16.2 Abbreviations and acronyms

ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways (Accord européen relatif au transport international des marchandises dangereuses par voies de navigation intérieures)

ADR: European agreement concerning the international carriage of dangerous goods by road (Accord européen relatif transport des marchandises dangereuses par route)

AGW: Occupational threshold limit value (Arbeitsplatzgrenzwert – Germany) AOX: Adsorbable Organic halogen compounds

ATEmix: Calculated acute toxicity estimate of mixture

BCF: Bio-Concentration Factor

CAS: Chemical Abstract Service

CLP: Classification, Labelling and Packaging

CMR: Substances classified as Carcinogenic, Mutagenic or toxic for Reproduction

CSR: Chemical Safety Report

DNEL: Derived No Effect Level

EC: European Commission

EC50: Effective Concentration 50%

ECHA: European Chemical Agency

EEC: European Economic Community

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

EWC: European Waste Catalogue

GHS: Globally Harmonised System of Classification, Labelling and Packaging of Chemicals

IATA: International Air Transport Association

ICAO: International Civil Aviation Organization

IC50: Inhibition Concentration 50%

IMDG Code: International Maritime Dangerous Goods Code

IMO: International Maritime Organization

LC50: Lethal concentration 50%

LD50: Lethal Dose 50%

LOAEL: Lowest Observed Adverse Effect Level

LOEL: Lowest observable effect level

MAK: Treshold limit values Germany (Maximale Arbeitsplatzkonzentration - DFG)

MARPOL: Convention for the Prevention of Marine Pollution from Ships

MVZ: molar ratio

n.a.: Not applicable

n.d.: Not determined

n.r.: Not relevant

NLP: No Longer Polymers

NOAEC: No Observed Adverse Effect Concentration

NOAEL: No Observed Adverse Effect Level

NOEC: No Observed Effect Concentration

NOEL: No Observed Effect Level

OEL: Occupational Exposure Limit

PBT: Persistent, bioaccumulative, toxic

PNEC: Predicted No Effect Concentration

RCP: Reciprocal calculation procedure

REACH: Registration, Evaluation and Authorization of Chemical)

RID: Regulations concerning the international carriage of dangerous goods by rail (Règlement International concernant le transport de marchandises dangereuses par chemin de fer)

STEL: Short-term Exposure Limit

SVHC: Substance of Very High Concern

# Safety Data Sheet

## according to Regulation (EC) No. 1907/2006 (REACH)



**Trade name :** Multi Primer 227  
Multigrund 227

**Revision date :** 27.03.2023

**Print date :** 27.03.2023

**Version (Revision) :** 23.0.0 (22.0.0)

---

TLV - TWA: Threshold Limit Value - Time Weighed Average  
VOC: Volatile Organic Compounds  
vPvB: Very persistent, very bioaccumulative.

### 16.3 Key literature references and sources for data

None

### 16.4 Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

The evaluation of hazard information of the product was carried out in accordance to Annex I of the REGULATION (EC) No 1272/2008 (CLP Regulation).

### 16.5 Relevant H- and EUH-phrases (Number and full text)

H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

### 16.6 Training advice

None

### 16.7 Additional information

None

---

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

---