

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



**Trade name :** 2C Uni-Polyester Filler 667  
2K-Uni-Polyesterspachtel 667  
**Revision date :** 24.02.2022  
**Print date :** 24.02.2022

**Version (Revision) :** 14.0.0 (13.0.0)

## SECTION 1: Identification of the substance/mixture and of the company/ undertaking

### 1.1 Product identifier

2C Uni-Polyester Filler 667  
2K-Uni-Polyesterspachtel 667

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

#### Relevant identified uses

##### Products Category [PC]

PC 9 - Coatings and paints, fillers, putties, thinners.

#### Uses advised against

There are no information about relevant identified uses of the product according to the Regulation (EC) No. 1907/2006 (REACH-Regulation), which are advised against. For using the product observe the information in the Technical data sheet of the product.

### 1.3 Details of the supplier of the safety data sheet

#### Supplier

Brillux GmbH & Co KG  
www.brillux.de

**Street :** Weseler Straße 401

**Postal code/City :** D - 48163 Münster

**Telephone :** +49 (0)251-7188-0

**Telefax :** +49 (0)251-7188-280

#### Information contact :

Electronic mail address of the well-informed person for safety data sheets:sdb@brillux.de

### 1.4 Emergency telephone number

Outside the business hours (9 a.m. to 5 p.m.):  
(Giftinformationszentrum-Nord, Göttingen, consultation in german or english language)  
Telephone: +49 (0)551-19240.

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

#### Classification according to Regulation (EC) No 1272/2008 [CLP]

Flam. Liq. 3 ; H226 - Flammable liquids : Category 3 ; Flammable liquid and vapour.

Skin Irrit. 2 ; H315 - Skin corrosion/irritation : Category 2 ; Causes skin irritation.

Eye Irrit. 2 ; H319 - Serious eye damage/eye irritation : Category 2 ; Causes serious eye irritation.

Skin Sens. 1 ; H317 - Skin sensitisation : Category 1 ; May cause an allergic skin reaction.

Repr. 2 ; H361d - Reproductive toxicity : Category 2 ; Suspected of damaging the unborn child.

STOT RE 2 ; H373 - STOT-repeated exposure : Category 2 ; May cause damage to organs through prolonged or repeated exposure.

### 2.2 Label elements

#### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

##### Hazard pictograms



Flame (GHS02) · Health hazard (GHS08) · Exclamation mark (GHS07)

##### Signal word

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



**Trade name :** 2C Uni-Polyester Filler 667  
2K-Uni-Polyesterspachtel 667  
**Revision date :** 24.02.2022  
**Print date :** 24.02.2022

**Version (Revision) :** 14.0.0 (13.0.0)

Warning

## Hazard components for labelling

STYRENE ; CAS No. : 100-42-5  
MALEIC ANHYDRIDE ; CAS No. : 108-31-6

## Hazard statements

H226 Flammable liquid and vapour.  
H361d Suspected of damaging the unborn child.  
H373 May cause damage to organs through prolonged or repeated exposure if inhaled.  
H315 Causes skin irritation.  
H317 May cause an allergic skin reaction.  
H319 Causes serious eye irritation.

## Precautionary statements

P102 Keep out of reach of children.  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P260 Do not breathe vapours.  
P271 Use only outdoors or in a well-ventilated area.  
P280 Wear protective gloves/protective clothing/eye protection/face protection.  
P314 Get medical advice/attention if you feel unwell.  
P308+P313 IF exposed or concerned: Get medical advice/attention.  
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.  
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].  
P501 Dispose of contents/container to approved disposal company or local collection.

## 2.3 Other hazards

The product does not contain any substances with endocrine-disrupting properties according to Article 59 Paragraph 1 or substances with endocrine-disrupting properties according to Regulations (EU) 2017/2100 or (EU) 2018/605. The product does not contain any substances, which fulfil the criteria for PBT or vPvB in accordance with the Annex XIII of the Regulation (EC) No 1907/2006 (REACH-Regulation).

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

#### Description

Mixture based on components, which are called following, and other components.

#### Hazardous ingredients

STYRENE ; REACH No. : 01-2119457861-32 ; EC No. : 202-851-5; CAS No. : 100-42-5

Weight fraction :  $\geq 5 - < 10$  %  
Classification 1272/2008 [CLP] : Flam. Liq. 3 ; H226 Asp. Tox. 1 ; H304 STOT RE 1 ; H372 Repr. 2 ; H361 Acute Tox. 4 ; H332 Skin Irrit. 2 ; H315 Eye Irrit. 2 ; H319 STOT SE 3 ; H335 Aquatic Chronic 3 ; H412

VINYLTOLUENE ; REACH No. : 01-2119622074-50 ; EC No. : 246-562-2; CAS No. : 25013-15-4

Weight fraction :  $\geq 2,5 - < 10$  %  
Classification 1272/2008 [CLP] : Flam. Liq. 3 ; H226 Asp. Tox. 1 ; H304 Acute Tox. 4 ; H332 Skin Irrit. 2 ; H315 Eye Irrit. 2 ; H319 Aquatic Chronic 3 ; H412

MALEIC ANHYDRIDE ; REACH No. : 01-2119472428-31 ; EC No. : 203-571-6; CAS No. : 108-31-6

Weight fraction :  $\geq 0,001 - < 0,1$  %  
Classification 1272/2008 [CLP] : Resp. Sens. 1 ; H334 STOT RE 1 ; H372 Skin Corr. 1B ; H314 Eye Dam. 1 ; H318 Acute Tox. 4 ; H302 Skin Sens. 1A ; H317

Specific Conc. Limits : Skin Sens. 1A ; H317: C  $\geq 0,001$  %

#### Additional information

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



**Trade name :** 2C Uni-Polyester Filler 667  
2K-Uni-Polyesterspachtel 667  
**Revision date :** 24.02.2022  
**Print date :** 24.02.2022

**Version (Revision) :** 14.0.0 (13.0.0)

For full text of Hazard- and EU Hazard-statements: see SECTION 16.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

#### General information

In all cases of doubt, or when symptoms persist, seek medical attention. Immediately remove all contaminated clothing. In case of unconsciousness: lay on side - call a doctor. Never give anything by mouth to an unconscious person. If medical advice is needed, have product container or label at hand.

#### Following inhalation

When symptoms persists, take the casualty into the fresh air and keep warm. Irregular breathing/no breathing: artificial respiration. Call a doctor and tell him the exactly substance.

#### In case of skin contact

Take off immediately all contaminated clothes. Wash away with soap and water and rinse. Do NOT use solvents or thinners. If skin irritation continues, consult a doctor.

#### After eye contact

Remove contact lenses, keep eyelids open. Rinse open eye immediately with plenty of running water. Seek medical advice if complaint continues.

#### Following ingestion

Drink water in small draught. Keep at rest. Do not induce vomiting. When swallowed immediately consult and show packing or label to physician.

### 4.2 Most important symptoms and effects, both acute and delayed

Potential symptoms: Headache, dizziness, giddiness, skin irritation and eye iriitation are possible. Allergic symptoms.

### 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

#### Suitable extinguishing media

In case of fire: Use alcohol resistant foam, CO<sub>2</sub>, powders or water spray for extinction.

#### Unsuitable extinguishing media

In case of fire: Do not use waterjet for extinction.

### 5.2 Special hazards arising from the substance or mixture

#### Hazardous combustion products

Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard.

### 5.3 Advice for firefighters

#### Special protective equipment for firefighters

At a fire caused by the product a breathing apparatus with an independent source of air is to have ready and to use if necessary for the firefighting. Personnel should wear protective clothings.

### 5.4 Additional information

Cool endangered containers with water in case of fire. Do not allow run-off from fire-fighting to enter drains or water courses.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Refer to protective measures listed in sections 7 and 8. Keep away from ignition sources on account of the organic solvent content and air room well. Do not inhale vapours. Avoid contact with eyes and skin.

# Safety Data Sheet

## according to Regulation (EC) No. 1907/2006 (REACH)



**Trade name :** 2C Uni-Polyester Filler 667  
2K-Uni-Polyesterspachtel 667

**Revision date :** 24.02.2022

**Print date :** 24.02.2022

**Version (Revision) :** 14.0.0 (13.0.0)

### 6.2 Environmental precautions

Do not empty into drains. If the product contaminates lakes, rivers or sewages, inform appropriate authorities in accordance with local regulations. Holding polluted washing water back and disposing of duly.

### 6.3 Methods and material for containment and cleaning up

#### For cleaning up

Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations (see section 13). The areas concerned cleaning with a customary water based cleaning agent, not using organic solvents if possible.

### 6.4 Reference to other sections

See Section 7 for information on safe handling.  
You find information about the safety equipment of persons in the section 8,  
information about the refuse disposal in section 13.

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

#### Protective measures

Ensure a good ventilation in room and working area. Prevent the creation of inflammable or explosive concentrations of vapour in air and avoid vapour concentrations higher than the OEL (=Occupational Exposure Limit). Only use the material in places where open light, fire and other flammable sources can be kept away. For personal protection see Section 8. Avoid contact with skin and eyes. Read label before use.

#### Measures to prevent fire

Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air. Avoid concentrations which form ignitable or explosive vapour and air mixtures. Likewise, avoid any concentration of vapour above the MAC-value. Keep away from ignition sources - No smoking. Ground/bond container and receiving equipment. Use explosion-proof pipes, electrical, ventilating and lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge.

#### Measures to prevent aerosol and dust generation

Not breathing in steams/aerosols.

#### Advices on general occupational hygiene

While working do not eat, drink or smoke. Wash hands and face before breaks and after work and take a shower if necessary. Immediately remove all contaminated clothing.

### 7.2 Conditions for safe storage, including any incompatibilities

#### Requirements for storage rooms and vessels

Electrical equipment should be protected to the appropriate standard. Floors should be of the conducting type. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Never use pressure to empty: container is not a pressure vessel. No smoking. Prevent unauthorized access. Do not store the product in lounge room. Keep only in the original container. Keep out of the reach of children. Store in a well-ventilated place. Keep cool.

#### Hints on joint storage

Keep away from oxidizing agents, from strongly alkaline and strongly acid materials. Store away from foodstuffs.

**Storage class (TRGS 510) :** 3

#### Further information on storage conditions

Keep container tightly sealed. Store at 5°-35°C. Containers should be kept dry and sealed. Suitable packing: Coated steel.

### 7.3 Specific end use(s)

For using the product observe the information in the Technical data sheet of the product.

#### Industrial sector specific solutions

**GISCODE :** This product can not be encoded in accordance with GISBAU.

## SECTION 8: Exposure controls/personal protection

**Trade name :** 2C Uni-Polyester Filler 667  
2K-Uni-Polyesterspachtel 667  
**Revision date :** 24.02.2022  
**Print date :** 24.02.2022

**Version (Revision) :** 14.0.0 (13.0.0)

## 8.1 Control parameters

### Occupational exposure limit values

STYRENE ; CAS No. : 100-42-5

Limit value type (country of origin) : TRGS 900 ( D )  
Limit value : 20 ppm / 86 mg/m<sup>3</sup>  
Peak limitation : 2(II)  
Remark : Y  
Version : 02.07.2009

VINYLTOLUENE ; CAS No. : 25013-15-4

Limit value type (country of origin) : TRGS 900 ( D )  
Limit value : 100 ppm / 490 mg/m<sup>3</sup>  
Peak limitation : 2(I)  
Version : 06.11.2015

MALEIC ANHYDRIDE ; CAS No. : 108-31-6

Limit value type (country of origin) : TRGS 900 ( D )  
Limit value : 0,02 ppm / 0,081 mg/m<sup>3</sup>  
Peak limitation : 1/=2=(I)  
Remark : Sa, Y  
Version : 06.11.2015

#### Remark

Taking into account the details mentioned in the TRGS 900 for the supervision of AGW.

### Biological limit values

STYRENE ; CAS No. : 100-42-5

Limit value type (country of origin) : TRGS 903 ( D )  
Mandelic acid plus phenylglyoxylic acid / Urine (U) / End of exposure or end of shift ;  
Parameter : At long term exposure: after several previous shifts  
Limit value : 600 mg/g Creatinine  
Version : 31.03.2004

### DNEL-/PNEC-values

#### DNEL/DMEL

MALEIC ANHYDRIDE ; CAS No. : 108-31-6

Limit value type : DNEL worker (local)  
Exposure route : Inhalation  
Exposure frequency : Short-term  
Limit value : 0,8 mg/m<sup>3</sup>  
Limit value type : DNEL worker (local)  
Exposure route : Dermal  
Exposure frequency : Short-term  
Limit value : 0,04 - 3  
Limit value type : DNEL worker (local and systemic)  
Exposure route : Inhalation  
Exposure frequency : Long-term  
Limit value : 0,4 mg/m<sup>3</sup>  
Limit value type : DNEL worker (local and systemic)  
Exposure route : Dermal  
Exposure frequency : Long-term  
Limit value : 0,04 mg/m<sup>3</sup>  
Limit value type : DNEL worker (systemic)  
Exposure route : Inhalation  
Exposure frequency : Short-term  
Limit value : 0,8 mg/m<sup>3</sup>  
Limit value type : DNEL worker (systemic)

# Safety Data Sheet

## according to Regulation (EC) No. 1907/2006 (REACH)



**Trade name :** 2C Uni-Polyester Filler 667  
2K-Uni-Polyesterspachtel 667

**Revision date :** 24.02.2022

**Print date :** 24.02.2022

**Version (Revision) :** 14.0.0 (13.0.0)

Exposure route : Dermal  
Exposure frequency : Short-term  
Limit value : 0,04 mg/m<sup>3</sup>

### PNEC

MALEIC ANHYDRIDE ; CAS No. : 108-31-6

Limit value type : PNEC (Aquatic, freshwater)  
Exposure route : Water (Including sewage plant)  
Limit value : 0,04281 mg/l  
Limit value type : PNEC (Aquatic, intermittent release)  
Limit value : 0,4281 mg/l  
Limit value type : PNEC (Aquatic, marine water)  
Exposure route : Water (Including sewage plant)  
Limit value : 0,00428 mg/l  
Limit value type : PNEC (Sediment, freshwater)  
Exposure route : Soil  
Limit value : 0,344 mg/kg  
Limit value type : PNEC (Sediment, marine water)  
Exposure route : Soil  
Limit value : 0,0334 mg/kg  
Limit value type : PNEC (Soil)  
Exposure route : Soil  
Limit value : 0,0415 mg/l  
Limit value type : PNEC (Sewage treatment plant)  
Limit value : 44,6 mg/l

## 8.2 Exposure controls

### Appropriate engineering controls

Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapour below the OEL (=Occupational Exposure Limit), suitable respiratory protection must be worn. Observe data available of section 7.

### Personal protection equipment

#### Eye/face protection

Use safety glasses. Having eye rinsing bottle at work ready.

#### Skin protection

##### Hand protection

At use as agreed a protective gloves from nitrile rubber, tested according to EN 374, with a material thickness 0,38 mm has to be used. Notes of the manufacturer have to be taken into account. Penetration time of the glove material: > = 8 h.

By longer or repeated contact the penetration times can be considerably shorter. The protective gloves should be replaced after the first wear out or a damage of the gloves. Gloves of cotton should be used under the gloves of polychloropren or nitrile rubber. After washing hands replace lost skin fat by fat containing skin creams.

##### Body protection

Using protective clothing.

#### Respiratory protection

Breathing protection equipment is not required in adequately ventilated places. A respiratory protection (combination filter A2-P3) is required by inadequate ventilation. Do not inhale the vapour.

### General information

Avoid contact with eyes and skin. Immediately remove all contaminated clothing. Do not eat or drink during work - no smoking. Wash hands before breaks and after work. Ensure a good ventilation in room and working area. Do not breathe vapour.

### Environmental exposure controls

The product should not reach waters and the ground. If the product contaminates lakes, rivers or sewages, inform appropriate authorities in accordance with local regulations.

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : 2C Uni-Polyester Filler 667  
2K-Uni-Polyesterspachtel 667  
Revision date : 24.02.2022  
Print date : 24.02.2022

Version (Revision) : 14.0.0 (13.0.0)

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

#### Appearance

Pasty.

Colour : conformable to product designation.

#### Odour

characteristic

#### Safety characteristics

Melting point/freezing point :	( 1013 hPa )	No data available	
Initial boiling point and boiling range :	( 1013 hPa )	145	°C
Decomposition temperature :	( 1013 hPa )	No data available	
Flash point :		31	°C
Auto-ignition temperature :		480	°C
Lower explosion limit :		1,2	Vol-%
Upper explosion limit :		8,9	Vol-%
Vapour pressure:	( 20 °C )	6	hPa
Density :	( 20 °C )	approx. 1,779	g/cm <sup>3</sup>
Solvent separation test :	( 20 °C )	<	3 %
Water solubility :	( 20 °C )	Not mixable	
pH :		not applicable	
log P O/W :		No data available	
Flow time :	( 20 °C )	No data available	DIN-cup 4 mm
Viscosity :	( 20 °C )	192000 - 204000	mPa*s
Kinematic viscosity :	( 40 °C )	no data available	
Solid content :		86,1	Weight-%
Relative vapour density :	( 20 °C )	No data available	
Maximum VOC content (EC) :		0	Weight-%
Flammable liquids :	The product is ignitable.		
Particle Characteristics :	No data available		

### 9.2 Other information

Other physical and chemical data have not been determined.

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

No dangers connected by a possible reactivity of the product are known to proper handling and storage.

### 10.2 Chemical stability

Stable under recommended storage and handling conditions (see section 7).

### 10.3 Possibility of hazardous reactions

Vapours can form explosive mixtures with air.

### 10.4 Conditions to avoid

To avoid formation of ignitable vapour and air mixtures ensure good ventilation (inter alia extraction system). Keep away from frost, heat and direct sunlight.

### 10.5 Incompatible materials

No dangerous reaction known. Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

### 10.6 Hazardous decomposition products

No dangerous decomposition product are known if stored and handled correctly. When exposed to high temperatures or

# Safety Data Sheet

## according to Regulation (EC) No. 1907/2006 (REACH)



**Trade name :** 2C Uni-Polyester Filler 667  
2K-Uni-Polyesterspachtel 667

**Revision date :** 24.02.2022

**Print date :** 24.02.2022

**Version (Revision) :** 14.0.0 (13.0.0)

in case of fire hazardous decomposition products such as carbon monoxide and dioxide, smoke, oxides of nitrogen, may produced.

### SECTION 11: Toxicological information

#### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

##### Acute toxicity

Acute toxicity:

- Acute oral toxicity: No data available;
- Acute dermal toxicity: No data available;
- Acute inhalation toxicity: No data available.

##### Acute oral toxicity

Parameter :	LD50 ( STYRENE ; CAS No. : 100-42-5 )
Exposure route :	Oral
Species :	Rat
Effective dose :	2650 mg/kg
Parameter :	LD50 ( STYRENE ; CAS No. : 100-42-5 )
Exposure route :	Oral
Species :	Mouse
Effective dose :	316 mg/kg
Parameter :	LD50 ( VINYLTOLUENE ; CAS No. : 25013-15-4 )
Exposure route :	Oral
Species :	Rat
Effective dose :	4000 mg/kg
Parameter :	LD50 ( MALEIC ANHYDRIDE ; CAS No. : 108-31-6 )
Exposure route :	Oral
Species :	Rat
Effective dose :	850 mg/kg
Parameter :	LD50 ( MALEIC ANHYDRIDE ; CAS No. : 108-31-6 )
Exposure route :	Oral
Species :	Mouse
Effective dose :	60 mg/kg

##### Acute inhalation toxicity

Parameter :	LD50 ( STYRENE ; CAS No. : 100-42-5 )
Exposure route :	Inhalation
Species :	Mouse
Effective dose :	90 mg/kg
Parameter :	LC50 ( VINYLTOLUENE ; CAS No. : 25013-15-4 )
Exposure route :	Inhalation
Species :	Mouse
Effective dose :	3020 mg/m <sup>3</sup>

##### Corrosion

Irritation:

- Skin contact: Skin irritation.
- Eye contact: Causes serious eye irritation.

##### Respiratory or skin sensitisation

The product is labeled as skin sensitizing.

##### CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

The product is classified as human reproductive toxic.

##### STOT-single exposure

Exposure to component solvents vapours concentration in excess of the stated occupational exposure limit may result in adverse health effect such as mucous membrane and respiratory system irritation, kidneys and liver damages, as well as leading the impairment of the central nervous system.



# Safety Data Sheet

## according to Regulation (EC) No. 1907/2006 (REACH)



**Trade name :** 2C Uni-Polyester Filler 667  
2K-Uni-Polyesterspachtel 667

**Revision date :** 24.02.2022

**Print date :** 24.02.2022

**Version (Revision) :** 14.0.0 (13.0.0)

Symptoms and signs include headache: dizziness, fatigue, muscular weakness, drowsiness and in extreme cases loss of consciousness.

The liquid splashed in the eyes may cause irritation and reversible damage.

### STOT-repeated exposure

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and absorption through the skin.

May cause damage to the organs through prolonged or repeated exposure.

### Aspiration hazard

The product contains substances, which are classified as aspiration toxicity, category 1, in accordance to the Regulation (EC) No. 1272/2008 (CLP-Regulation) in their pure form.

The product is not classified as aspiration toxicity, category 1, because of the higher viscosity (> 20,5 mm<sup>2</sup>/s at 40°C) and the used concentration of the substances.

## 11.2 Information on other hazards

### Endocrine disrupting properties

The product does not contain any substances with endocrine-disrupting properties according to Article 59 Paragraph 1 or substances with endocrine-disrupting properties according to Regulations (EU) 2017/2100 or (EU) 2018/605.

### Other adverse effects

This product is unlikely to harm health, given normal and proper handling and hygienic precautions.

### Additional information

The product is classified in toxicological terms on the basis of the results of the calculation procedure outlined within the Regulation (EC) No 1272/2008 (CLP-Regulation), listed in sections 2 and 3.

At proper dealing and use as agreed the product does not cause any effects bad for health after our experiences and the information submitted to us.

## SECTION 12: Ecological information

### 12.1 Toxicity

No information available.

### 12.2 Persistence and degradability

These are not data available about the potential of the product concerning its persistency and degradability.

### 12.3 Bioaccumulative potential

These are not data available about the bio accumulation potential of the product.

### 12.4 Mobility in soil

These are not data available about the potential of the product concerning its mobility in the ground.  
A penetrating into soil, waters and sewage system should be prevented.

### 12.5 Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

### 12.6 Endocrine disrupting properties

The product does not contain any substances with endocrine-disrupting properties according to Article 59 Paragraph 1 or substances with endocrine-disrupting properties according to Regulations (EU) 2017/2100 or (EU) 2018/605.

### 12.7 Other adverse effects

Acute or chronic damages to water organisms by the product in the aquatic environment are not expected.

### 12.8 Additional ecotoxicological information

Avoid exposing into ground, waterways and drainage.

The classification of the product is based on summation of classified components according to the Regulation (EC) No 1272/2008 (CLP-Regulation). See details in sections 2 and 3.

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



**Trade name :** 2C Uni-Polyester Filler 667  
2K-Uni-Polyesterspachtel 667

**Revision date :** 24.02.2022

**Print date :** 24.02.2022

**Version (Revision) :** 14.0.0 (13.0.0)

## Directive 2008/98/EC (Waste Framework Directive)

### Before intended use

Dispose of contents/container to approved disposal company or local collection according to the local regulations. Packaging with not dry uped residues have to droped at official collecting sites. Packaging with dry uped residues can be disposed together with household garbage or building site garbage. Do not empty into waters or drains.

### Waste codes/waste designations according to EWC/AVV

For the product:  
Disposal-definition No. (AVV-Code): 08 04 09\* - Waste adhesives and sealants containing organic solvents or other hazardous substances.

### After intended use

Only empty packaging can be transfered to recycling. Uncleaned packaging must be disposed of in the same manner as the medium.

### Waste codes/waste designations according to EWC/AVV

For the uncleaned packaging:  
Disposal-definition No.: 15 01 10 \* packings which contain dangerous substances or are polluted by dangerous substances.

## SECTION 14: Transport information

### 14.1 UN number

UN 3269

### 14.2 UN proper shipping name

#### Land transport (ADR/RID)

POLYESTER RESIN KITS

#### Sea transport (IMDG)

POLYESTER RESIN KITS

#### Air transport (ICAO-TI / IATA-DGR)

POLYESTER RESIN KITS

### 14.3 Transport hazard class(es)

#### Land transport (ADR/RID)

**Class(es) :** 3  
**Classification code :** F3  
**Hazard identification number (Kemler No.) :** 30  
**Tunnel restriction code :** E  
**Special provisions :** LQ 51 · E 0  
**Hazard label(s) :** 3

#### Sea transport (IMDG)

**Class(es) :** 3  
**Hazard label(s) :** 3

#### Air transport (ICAO-TI / IATA-DGR)

**Class(es) :** 3  
**Hazard label(s) :** 3

### 14.4 Packing group

III

### 14.5 Environmental hazards

**Land transport (ADR/RID) :** No

**Sea transport (IMDG) :** No

**Air transport (ICAO-TI / IATA-DGR) :** No

### 14.6 Special precautions for user

None

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : 2C Uni-Polyester Filler 667  
2K-Uni-Polyesterspachtel 667  
Revision date : 24.02.2022  
Print date : 24.02.2022

Version (Revision) : 14.0.0 (13.0.0)

## 14.8 Additional information

ADR/RID: Limited quantities.

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

#### EU legislation

##### Other regulations (EU)

##### Directive 2004/42/EC on the limitation of emissions of volatile organic compounds

The product is not subject to the EU guideline 2004/42/EC about the limitation of the issues of brief organic connections due to the use of organic solvents in certain colours and varnishes.

##### National regulations

##### Water hazard class

Classification according to AwSV - Class : 2 (Obviously hazardous to water)

##### Additional information

The product is classified as a solid substance according to the criteria of the Penetrometer test (ADR, part 2, section 2.3.4) and also fulfils the criteria for solid substances according to the TRwS 779 number 2.1.1.

Maternity regulations and Young Persons Employment Act are to take into account.

### 15.2 Chemical Safety Assessment

A chemical safety assessments was not carried out.

## SECTION 16: Other information

### 16.1 Indication of changes

None

### 16.2 Abbreviations and acronyms

ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways (Accord européen relatif au transport international des marchandises dangereuses par voies de navigation intérieures)  
ADR: European agreement concerning the international carriage of dangerous goods by road (Accord européen relatif transport des marchandises dangereuses par route)  
AGW: Occupational threshold limit value (Arbeitsplatzgrenzwert – Germany) AOX: Adsorbable Organic halogen compounds  
ATEmix: Calculated acute toxicity estimate of mixture  
BCF: Bio-Concentration Factor  
CAS: Chemical Abstract Service  
CLP: Classification, Labelling and Packaging  
CMR: Substances classified as Carcinogenic, Mutagenic or toxic for Reproduction  
CSR: Chemical Safety Report  
DNEL: Derived No Effect Level  
EC: European Commission  
EC50: Effective Concentration 50%  
ECHA: European Chemical Agency  
EEC: European Economic Community  
EINECS: European Inventory of Existing Commercial Chemical Substances  
ELINCS: European List of Notified Chemical Substances  
EWC: European Waste Catalogue  
GHS: Globally Harmonised System of Classification, Labelling and Packaging of Chemicals  
IATA: International Air Transport Association  
ICAO: International Civil Aviation Organization  
IC50: Inhibition Concentration 50%  
IMDG Code: International Maritime Dangerous Goods Code  
IMO: International Maritime Organization  
LC50: Lethal concentration 50%

# Safety Data Sheet

## according to Regulation (EC) No. 1907/2006 (REACH)



**Trade name :** 2C Uni-Polyester Filler 667  
2K-Uni-Polyesterspachtel 667

**Revision date :** 24.02.2022

**Print date :** 24.02.2022

**Version (Revision) :** 14.0.0 (13.0.0)

LD50: Lethal Dose 50%  
LOAEL: Lowest Observed Adverse Effect Level  
LOEL: Lowest observable effect level  
MAK: Treshold limit values Germany (Maximale Arbeitsplatzkonzentration - DFG)  
MARPOL: Convention for the Prevention of Marine Pollution from Ships  
MVZ: molar ratio  
n.a.: Not applicable  
n.d.: Not determined  
n.r.: Not relevant  
NLP: No Longer Polymers  
NOAEC: No Observed Adverse Effect Concentration  
NOAEL: No Observed Adverse Effect Level  
NOEC: No Observed Effect Concentration  
NOEL: No Observed Effect Level  
OEL: Occupational Exposure Limit  
PBT: Persistent, bioaccumulative, toxic  
PNEC: Predicted No Effect Concentration  
RCP: Reciprocal calculation procedure  
REACH: Registration, Evaluation and Authorization of Chemical)  
RID: Regulations concerning the international carriage of dangerous goods by rail (Règlement International concernant le transport de marchandises dangereuses par chemin de fer)  
STEL: Short-term Exposure Limit  
SVHC: Substance of Very High Concern  
TLV - TWA: Threshold Limit Value - Time Weighed Average  
VOC: Volatile Organic Compounds  
vPvB: Very persistent, very bioaccumulative.

### 16.3 Key literature references and sources for data

None

### 16.4 Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

The evaluation of hazard information of the product was carried out in accordance to Annex I of the REGULATION (EC) No 1272/2008 (CLP Regulation).

### 16.5 Relevant H- and EUH-phrases (Number and full text)

H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	May cause respiratory irritation.
H361	Suspected of damaging fertility or the unborn child.
H372	Causes damage to organs through prolonged or repeated exposure.
H412	Harmful to aquatic life with long lasting effects.

### 16.6 Training advice

None

### 16.7 Additional information

None

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of

**Safety Data Sheet**  
**according to Regulation (EC) No. 1907/2006 (REACH)**



**Trade name :** 2C Uni-Polyester Filler 667  
2K-Uni-Polyesterspachtel 667  
**Revision date :** 24.02.2022  
**Print date :** 24.02.2022

**Version (Revision) :** 14.0.0 (13.0.0)

---

mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

---