according to Regulation (EC) No. 1907/2006 (REACH)



Trade name: Antigraffiti-Pulver PU 5961, Pigmentiert (SORTE 5961)

Revision date: 17.12.2019 **Version (Revision):** 9.0.0 (8.0.0)

Print date: 17.12.2019

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier

Antigraffiti-Pulver PU 5961, Pigmentiert (SORTE 5961)

1.2 Relevant identified uses of the substance or mixture and uses advised against

Powder coating. Intended purpose see technical data sheet.

Relevant identified uses

Product Categories [PC]

PC9 - Coatings and paints, fillers, putties, thinners

Remark

The product is intended for professional use.

1.3 Details of the supplier of the safety data sheet

Supplier (manufacturer/importer/only representative/downstream user/distributor)

Brillux GmbH & Co. KG, Industrielack www.brillux-industrielack.de

Street: Otto-Hahn-Straße 14

Postal code/city: D-59423 Unna Telephone: +49 2303 8805-0 Telefax: +49 2303 8805-119

Information contact: E-mail address of the competent person for safety data sheets: sdb@brillux-

industrielack.de

1.4 Emergency telephone number

Giftinformationszentrum-Nord (poisons centre), consultation in german and english

Telephone: +49 551 19 24 0

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]

None

Additional information

The mixture is classified as not hazardous according to regulation (EC) No 1272/2008 [CLP].

2.2 Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Precautionary statements

P260 Do not breathe dust/fume/gas/mist/vapours/spray. **Special rules for supplemental label elements for certain mixtures**

EUH210 Safety data sheet available on request.

2.3 Other hazards

Other adverse effects

While baking the powder coat caprolactam (CAS-No. 105-60-2, EG-No. 203-313-2, classification: Acute Tox. 4, H302; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335) is released. Caprolactam is harmful by inhalation and if swallowed and is irritating to eyes, respiratory system and skin. Sufficient suction of the air in the oven is necessary.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Page: 1/8

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name: Antigraffiti-Pulver PU 5961, Pigmentiert (SORTE 5961)

Revision date: 17.12.2019 **Version (Revision):** 9.0.0 (8.0.0)

Print date : 17.12.2019

Hazardous ingredients

None

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

When in doubt or if symptoms are observed, get medical advice. Change contaminated, saturated clothing. If unconscious place in recovery position and seek medical advice.

Following inhalation

Remove casualty to fresh air and keep warm and at rest. If breathing is irregular or stopped, administer artificial respiration. In case of respiratory tract irritation, consult a physician.

In case of skin contact

Wash immediately with: Water and soap Do not wash with: Solvents/Thinner

After eye contact

Rinse immediately carefully and thoroughly with eye-bath or water. In case of eye irritation consult an ophthalmologist.

After ingestion

If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention. Keep at rest. Do NOT induce vomiting. No direct artificial respiration to be given by first aider.

4.2 Most important symptoms and effects, both acute and delayed

No information available.

4.3 Indication of any immediate medical attention and special treatment needed

None

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Extinguishing powder, alcohol resistant foam, carbon dioxide (CO_2) , water spray. The fire fighting for manuell and self-acting powder coating systems conformable BGI 764 the extingshent agent CO_2 can be used by movable tool and fight fire extingquishing system. For using other extingshent agent than CO_2 the effectiveness must be proved.

Unsuitable extinguishing media

Full water jet, inert gas with high pressure.

5.2 Special hazards arising from the substance or mixture

Hazardous combustion products

In case of fire may be liberated: Nitrogen oxides (NOx), carbon monoxide (CO), carbon dioxide (CO₂) and pyrolysis products, toxic.

5.3 Advice for firefighters

Special protective equipment for firefighters

Use suitable breathing apparatus.

5.4 Additional information

Burning produces heavy smoke. Use water spray jet to protect personnel and to cool endangered containers. Do not allow run-off from fire-fighting to enter drains or water courses.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Remove all sources of ignition. See protective measures under point 7 and 8. Avoid dust formation. Do not inhale product dusts.

6.2 Environmental precautions

Page: 2/8

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name: Antigraffiti-Pulver PU 5961, Pigmentiert (SORTE 5961)

Revision date: 17.12.2019 **Version (Revision):** 9.0.0 (8.0.0)

Print date: 17.12.2019

Do not allow to enter into surface water or drains.

6.3 Methods and material for containment and cleaning up

For cleaning up

Take up dust-free and set down dust-free. Use approved industrial vacuum cleaner for removal. (Vacuum cleaner construction B1, appropriate to suck up combustible dust). Treat the recovered material as prescribed in the section on waste disposal.

6.4 Reference to other sections

None

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Protective measures

Avoid: Generation/formation of dust, dust deposits, inhalation of dust/particles. Only use the material in places where open light, fire and other flammable sources can be kept away. If handled uncovered, arrangements with local exhaust ventilation should be used if possible. If local exhaust ventilation is not possible or not sufficient, the entire working area must be ventilated by technical means.

Measures to prevent fire

Dust can form an explosive mixture with air. Take precautionary measures against static discharges. Wear anti-static footwear and clothing Use only antistatically equipped (spark-free) tools.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Floors should be impervious and easy to clean.

Hints on joint storage

Storage class (TRGS 510): 11 Do not store together with

Strong acid, strong alkali, oxidising agent, food and feedingstuffs.

Further information on storage conditions

Do not store at temperatures above : 25 °C

Protect against: Humidity.

7.3 Specific end use(s)

Powder coating. Intended purpose see technical data sheet.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

While baking the powder coat caprolactam (CAS-No. 105-60-2, EG-No. 203-313-2, classification: Acute Tox. 4, H302; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335) is released. Caprolactam is harmful by inhalation and if swallowed and is irritating to eyes, respiratory system and skin. Sufficient suction of the air in the oven is necessary.

Occupational exposure limit values

EPSILON-CAPROLACTAM; CAS No.: 105-60-2

Limit value type (country of origin): TRGS 900 (D)

Parameter: E: inhalable fraction

 Limit value :
 5 mg/m³

 Peak limitation :
 2(I)

 Remark :
 Y

 Version :
 29.03.2019

GENERAL LIMIT VALUE FOR DUST

Page: 3 / 8

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Antigraffiti-Pulver PU 5961, Pigmentiert (SORTE 5961)

Revision date: 17.12.2019 **Version (Revision):** 9.0.0 (8.0.0)

Print date : 17.12.2019

Peak limitation: 2(II)
Version: 29.03.2019
Limit value type (country of origin): TRGS 900 (D)
Parameter: E: inhalable fraction

Limit value: 10 mg/m³
Peak limitation: 2(II)
Version: 29.03.2019

8.2 Exposure controls

Personal protection equipment

Eye/face protection

Suitable eye protection

Dust protection eye glasses

Remark

Note DGUV-Rule 112-192.

Skin protection

Hand protection

Suitable gloves type: Disposable gloves. Gloves with long cuffs

Required properties: dust-tight. antistatic.

Remark: After washing hands replace lost skin fat by fat containing skin creams. Note DGUV-Rule 112-195. Note

TRGS 401.

Body protection

Personel should wear protective clothings and all parts of the body should be washed after contact. Care should be taken in the selection of protective clothing to ensure that inflammation and irritation of the skin at neck and wrists through contact with the powder is avoided.

Recommended material: Natural fibres (e.g. cotton), heat-resistant synthetic fibres.

Remark: Note DGUV-Rule 112-189. Note TRGS 401.

Respiratory protection

Respiratory protection necessary at: insufficient exhaust

Suitable respiratory protection apparatus

Use breathing filter P2 (particle).

European Committee for Standardization (CEN) standards EN 136, 140 and 405 provide respirator masks and EN 149 and 143 provide filter recommendations.

Remark

Observe the wear time limits according GefStoffV in combination with the rules for using respiratory protection apparatus (BGR 190). Note TRGS 402.

General health and safety measures

Used working clothes should not be worn outside the work area.

Occupational exposure controls

Technical measures to prevent exposure

Technical measures and the application of suitable work processes have priority over personal protection equipment.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

Physical state : Powder (1-150 μm) **Colour :** According to product identification.

Odour

Poor, characteristic.

Safety relevant basis data

Melting point/melting range : > 50 °C **Initial boiling point and boiling** (1013 hPa) not applicable

Page: 4 / 8

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Antigraffiti-Pulver PU 5961, Pigmentiert (SORTE 5961)

Revision date: 17.12.2019 **Version (Revision):** 9.0.0 (8.0.0)

Print date : 17.12.2019

range:

Decomposition temperature : > 250 °C **Flash point :** not applicable

 Upper explosion limit:
 No data available

 Vapour pressure:
 (50 °C)
 No data available

Density: (20 °C) 1,2 - 1,8 g/cm³

Water solubility: (20 °C) insoluble

pH:No data availablelog P O/W:not relevantViscosity:(23 °C)not applicable

Cinematic viscosity: (40 °C) not applicable

Solid content: 100 Wt %

Odour threshold: not relevant

Relative vapour density : (20 °C) not applicable **Vapourisation rate :** not applicable

Flammable solids: Not highly flammable.

Oxidising solids: Not oxidising.

9.2 Other information

The physical specifications are approximate values and refer to the used safety relevant component(s).

SECTION 10: Stability and reactivity

10.1 Reactivity

No information available.

10.2 Chemical stability

Stable under recommended storage and handling conditions (see section 7).

10.3 Possibility of hazardous reactions

No information available.

10.4 Conditions to avoid

No information available.

10.5 Incompatible materials

No information available.

10.6 Hazardous decomposition products

Does not decompose when used for intended uses.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute effects

Acute oral toxicity

Parameter: ATEmix calculated

Exposure route : Oral
Effective dose : not relevant

Acute dermal toxicity

Parameter: ATEmix calculated

Exposure route : Dermal
Effective dose : not relevant

Acute inhalation toxicity

Parameter: ATEmix calculated Exposure route: Inhalation (dust/mist)

Effective dose : not relevant

Page: 5 / 8

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Antigraffiti-Pulver PU 5961, Pigmentiert (SORTE 5961)

Revision date: 17.12.2019 **Version (Revision):** 9.0.0 (8.0.0)

Print date: 17.12.2019

11.3 Symptoms related to the physical, chemical and toxicological characteristics

In case of skin contact

Powder coatings can cause localised skin irritation in folds of the skin or in contact with tight clothing.

SECTION 12: Ecological information

12.1 Toxicity

No information available.

12.2 Persistence and degradability

Abiotic degradation

Mechanical separation in a suitable sewage plant is possible.

Biodegradation

In accordance with the required stability the product is poorly biodegradable.

12.3 Bioaccumulative potential

No information available.

12.4 Mobility in soil

No information available.

12.5 Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6 Other adverse effects

No information available.

12.7 Additional ecotoxicological information

Additional information

Do not allow uncontrolled discharge of product into the environment.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process. Dispose according to legislation.

Product/Packaging disposal

Waste codes/waste designations according to EWC/AVV

Waste code product

EWC-Code: 08 02 01.

Waste treatment options

Appropriate disposal / Package

Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

13.2 Additional information

Note sections 7 and 8.

SECTION 14: Transport information

14.1 UN number

No dangerous good in sense of these transport regulations.

14.2 UN proper shipping name

No dangerous good in sense of these transport regulations.

14.3 Transport hazard class(es)

No dangerous good in sense of these transport regulations.

14.4 Packing group

Page: 6 / 8

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Antigraffiti-Pulver PU 5961, Pigmentiert (SORTE 5961)

Revision date: 17.12.2019 **Version (Revision):** 9.0.0 (8.0.0)

Print date : 17.12.2019

No dangerous good in sense of these transport regulations.

14.5 Environmental hazards

No dangerous good in sense of these transport regulations.

14.6 Special precautions for user

None

SECTION 15: Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation

Other regulations (EU)

Restrictions of occupation

Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

National regulations

Technische Anleitung Luft (TA-Luft)

Weight fraction (Number 5.2.5. I): 0,5 - 0,99 %

Water hazard class (WGK)

Class: 1 (Slightly hazardous to water) Classification according to AwSV

Other regulations, restrictions and prohibition regulations

Note TRGS 001. Note TRGS 400.

15.2 Chemical safety assessment

A chemical safety assessment has not been carried out.

SECTION 16: Other information

16.1 Indication of changes

None

16.2 Abbreviations and acronyms

TRGS: German Technical Rule for Hazardous Substances. BGR(I): Rule (Information) from the german employers liability insurance association. DGUV: German Statutory Accident Insurance. AwSV: Ordinance on plants for the handling of substances hazardous to water. VCI: German chemical industry association. EWC: European Waste Catalogue.

16.3 Key literature references and sources for data

None

$^{16.4}$ Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

Calculation method.

16.5 Relevant H- and EUH-phrases (Number and full text)

None

16.6 Training advice

None

16.7 Additional information

None

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

Page: 7 / 8

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Antigraffiti-Pulver PU 5961, Pigmentiert (SORTE 5961)

Revision date: 17.12.2019 **Version (Revision):** 9.0.0 (8.0.0)

Print date : 17.12.2019

Page: 8 / 8